## STEELMASTER STANDARD FULL HYDRAULIC PANBRAKE

Offering A Hydraulic Operated Panbrake At The Right Price.











## **FEATURES**

- full hydraulic clamp & fold for efficient heavy duty operation.
- machine constructed from heavy plate steel with continuous welded seams to ensure high structural rigidity
- high load capacity dual spherical plane bearings utilised at bending beam pivots and over centre clamp bearings ensure long low maintenance operation through it working life
- segmented bending fingers made from harder material to maximize life and accuracy
- high quality componentry ensures reliable performance for years of continuous operation
- large hydraulic oil reservoir to maintain low oil temperature for high production
- infinitely adjustable bending angle control from 0-125 degrees
- quick set feature for angle bending
- precise manual inching of bending beam for efficient operation
- low voltage control wiring for safety
- CE Compliant

TECHNICAL DATA	(model)	SM-FHPB2502	SM-FHPB2504	SM-FHPB3204	SM-FHPB4004	SM-FHPB2506
sku	(#)	18-0146	18-0110	18-0113	18-0116	18-0118
folding length	(mm)	2450	2500	3200	4000	2500
max. thickness	(mm)	2.5	4	4	4	5
max. bending angle	(deg)	125°	130°	130°	130°	130°
largest box depth:	(mm)	145	160	160	160	160
max lift of top beam	(mm)	200	200	200	200	200
motor	(kw)	3	4	4	5.5	5.5
weight	(kg)	2750	3300	3800	4950	4500
dimensions	(mm)	3050 x 950 x 1550	3050 x 850 x 1550	3800 x 900 x 1550	4400 x 950 x 1550	3050 x 1000 x 1600
PRICE	(AUD)	\$	\$	\$	\$	\$