

STEELMASTER ELECTRO SHEAR

Fast And Efficient Shearing For use In Both Jobbing And Production. Power Backgauge Model Available.



SM-EMS2500-3.2



Flat Infeed Table



Slotted Viewing Holes



Rear Laser Guarding

EQUIPMENT & ACCESSORIES SUPPLIED

Top and bottom blades, remote foot control pedal, squaring arm, sheet supports, tools and manual

Features

- | heavy steel weldment construction for maximum stability
- | quiet operation with brake motor, all components run on maintenance free bearings
- | parallel blade guides ensure high cutting precision
- | hardened and ground high quality HSS blades fitted
- | calibrated squaring arm with front sheet supports
- | hold-down system with slip-resistant rubber coating and front safety guard
- | quick action blade-gap setting
- | roving foot-pedal operation
- | heavy duty backgauge
- | CE compliant

Technical Features

- | Front sheet supports
- | Rear safety net guarding
- | Remote foot pedal operation
- | Frame is constructed of whole welded steel, compact construction with light weight and good rigidity

TECHNICAL DATA	(model)	SM-EMS1270-3.2	SM-EMS2500-3.2
sku (manual back gauge)	(#)	17-0201	17-0205
sku (power back gauge)	(#)	17-0201PWR	17-0205PWR
thickness of material	(mm)	3.2	3.2
width of material	(mm)	1270	2500
back gauge depth	(mm)	0 ~ 650	0 ~ 650
shear angle	(deg)	1° 30'	1° 30'
bed height	(mm)	800	800
strokes per minute	(#)	47	47
motor power	(kw/v)	5.5 / 415	7.5 / 415
weight (nt)	(kg)	1450	2200
dimensions (l x w x h)	(mm)	1860 x 1100 x 1180	3124 x 1100 x 1180
price - manual	(AUD)	\$	\$
price - power	(AUD)	\$	\$

3 ph /415 volt machinery do not come fitted with plugs as standard. GST is NOT included in the listed prices

