

STEELMASTER SM-GHC40A GEARED HEAD DRILL

Steelmaster Geared Head Drill Offering Cost Effective Drilling With Power Feed & Coolant.

FEATURES

- manual feed spindle with fine feed
- power feed fitted
- quick action tapping feature fitted
- emergency stop switch
- draw bar (M16) spindle for milling
- large MT4 (morse taper)
- forward and reverse operation
- adjustable depth stop fitted
- digital depth display with zero position
- swivelling table offering flexibility
- ideal workshop drill
- head swivels 360 degrees
- heavy duty tapered roller bearing spindle offering stability
- positive spindle lock fitted
- perspex safety guard
- coolant system supplied standard
- gear drive with low noise
- 240 or 415 Volt operation
- CE compliant

UNIQUE FEATURES

"making ours unique!"



- Power quill feed
- Die-cast handles
- Digital display
- LED worklight
- Intergrated Coolant



TECHNICAL DATA	(model)	SM-GHC40A	SM-GHC40A
sku	(#)	11-0209	11-0203
drilling capacity (max)	(mm)	40	40
threading capacity (max)	(metric)	22	22
spindle travel	(mm)	120	120
power spindle feed	(mm/rev)	0.1 ~ 0.3 / 3	0.1- 0.3 / 3
spindle holding fixture	(mt)	4	4
distance spindle / table (max)	(mm)	715	715
distance spindle / base (max)	(mm)	1180	1180
throat depth	(mm)	297	297
working table surface (l x w)	(mm)	500 x 460	500 X 460
t-slot size	(mm)	14	14
drilling table swivel	(deg)	±90°	±90°
spindle speeds	(rpm)	75 ~ 1600	75 ~ 1600
number of steps	(steps)	6	6
upright diameter	(mm)	115	115
motor power	(kw/V)	1.5 / 240	1.5 / 415
dimensions - (l x w x h)	(mm)	740 x 760 x 1870	740 x 760 x 1870
weight (nt)	(kg)	420	420
PRICE	(AUD)	\$	\$

OPTIONAL - 58 PIECE CLAMPING KIT				
SKU	T-SLOT SIZE (MM)	THREAD (MM)	WEIGHT (KG)	PRICE
13+0126	14	M12	8.5	\$

EQUIPMENT & ACCESSORIES SUPPLIED

Protective safety guard, Drawbar, 13mm Drill chuck, Arbor, MT4- 3 sleeve, T-Bolts, Toolkit & Manual.

3 ph /415 volt machinery do not come fitted with plugs as standard. GST is NOT included in the listed prices

